



2017 Vehicle Safety Inspection Form

This inspection must be completed within 30 days of the event and signed by both the inspector and participant(s)

SECTION 1 – To be completed by Dealer or other automotive inspection facility-initial each item

Car Make & Model:	Color:	Year:
-------------------	--------	-------

Brake Rotors <i>Thickness exceeds minimum. No connecting cracks between drilled holes or between hole and edge of rotor.</i>	Fluid Lines, Hoses & Fittings <i>Zero leakage, flex hoses not brittle or dry-rotted, properly supported, connections secure for all oil and coolant lines.</i>
Brake Pads <i>Minimum 50% of new pad thickness on both inboard and outboard pads.</i>	Fuel Lines, Hoses & Fittings <i>Zero leakage, flex hoses not brittle or dry-rotted, properly supported, connections secure.</i>
Brake Fluid, Brake Lines & Brake Pedal <i>Fluid flushed and bled within 6 mo., both fixed and flexible brake lines sound and pedal returns to resting position.</i>	Battery <i>Properly secured, no leakage and positive terminal protected.</i>
Wheel Bearings <i>Properly adjusted; no excessive play.</i>	Exhaust System <i>No leaks, no loose components, properly supported.</i>
Wheels <i>Structurally sound ~ no cracks or bends whatsoever. Steel lug nuts recommended. Airtight valve caps in place.</i>	Windshield & Mirrors <i>No cracks in windshield. At least one securely mounted rear-view mirror.</i>
Tires <i>No visible damage. Minimum tread 2/32" for tires produced with tread. DOT date stamp no more than 6 (six) years old.</i>	Basic Structural Strength <i>No modifications or corrosion to basic structure of the car that could compromise strength.</i>
Shock Absorbers & Bump Stops <i>All components securely attached. No leaks and effective damping. Bump stops intact and in good condition.</i>	Brake Lights <i>All OEM brake light assemblies functional.</i>
Ball Joints & Tie Rods <i>In good condition and zero play.</i>	Motor Mounts, Engine Belts & Acc. Belts <i>Secure, structurally sound and belts properly tensioned.</i>
Sway Bars & Attachment Points <i>Structurally sound and bushings complete.</i>	Fire Extinguisher <i>Not required but recommended. If installed, must have metal-to-metal attachment bracketing.</i>
Steering <i>No excessive play in any component, no leaking pumps, hoses, lines or steering rack.</i>	Harness Restraint System <i>If installed, must be a proper "Restraint System" See supplemental inspection guide.</i>
Roll-over Protection <i>All non-fixed-roof cars must have roll-over protection. See supplemental inspection guide.</i>	Leaks <i>No leaks of any kind ~ oil, fuel, brake or coolant.</i>
Inspection Performed at (Official Stamp Only):	Inspection Date:
	Inspector Name:
	Phone Number: ()
	Inspector Signature:

Section 2 – To be completed by Participant(s)

By signing this form I certify that a qualified mechanic has performed the above inspections and any deficiencies have been corrected. I acknowledge that I am solely responsible for the condition and suitability of this vehicle and helmet for this event. I release ARPCA and any person involved with this event from any liability arising for a failure of this vehicle or helmet for any reason, including the failure of the items listed on this form.

I (we) certify that my helmet is Snell 2010 or 2015

compliant:

Print Driver #1 Name:	Driver # 1 Signature:
Print Driver #2 Name:	Driver # 2 Signature: